According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



terralin® liquid No Change Service! Version **Revision Date:** Date of last issue: 06.09.2022 06.07 07.08.2024 SECTION 1: Identification of the substance/mixture and of the company/undertaking **1.1 Product identifier** Trade name : terralin® liquid 1.2 Relevant identified uses of the substance or mixture and uses advised against Use of the Sub-: Disinfectants, Medical device stance/Mixture **Recommended restrictions** : Reserved for industrial and professional use. on use 1.3 Details of the supplier of the safety data sheet Producer Schülke & Mayr GmbH : Robert-Koch-Str. 2 22851 Norderstedt Germany Telephone: +49 (0)40/ 52100-0 Telefax: +49 (0)40/ 52100318 mail@schuelke.com www.schuelke.com Supplier Schülke & Mayr UK Ltd. Cygnet House 1, Jenkin Road Sheffield S9 1AT United Kingdom Telephone: +44 114 254 35 00 Telefax: +44 114 254 35 01 mail.uk@schulke.com E-mail address of person **Application Specialists** : responsible for the +49 (0)40/ 521 00 666 SDS/Contact person AD@schuelke.com

1.4 Emergency telephone number

Emergency telephone num-	:	Carechem 24 International:+44 1235 239670
ber		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

schülke ->

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H226 Flammable liquid and vapour.H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.	
Precautionary statements	:	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapours/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection. 	
		Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention.	

Hazardous components which must be listed on the label: propan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Vapours may form explosive mixtures with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Solution of the following substances with harmless additives.

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

terralin® liquid No Change Service!

Version 06.07	Revision Date: 07.08.2024	Date of last issue: 06.09.2022		
propan-1-ol		71-23-8 200-746-9 603-003-00-0 01-2119486761-29- XXXX	Flam. Liq. 2; H225 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
ethanol		64-17-5 200-578-6 603-002-00-5 01-2119457610-43- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 20 - < 30


schülke ->

For explanation of abbreviations see section 16.

SECTION 4: First aid measures


4.1 Description of first aid measures

General advice	:	Take off all contaminated clothing immediately.		
If inhaled	:	Move to fresh air. If symptoms persist, call a physician.		
In case of skin contact	:	Wash off with plenty of water. If symptoms persist, call a physician.		
In case of eye contact	:	In case of eye contact, remove contact lens and rinse imme- diately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.		
If swallowed	:	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Obtain medical attention.		
4.2 Most important symptoms ar	nd e	effects, both acute and delayed		
Symptoms	:	Treat symptomatically.		
Risks	:	Causes serious eye irritation. May cause drowsiness or dizziness.		
4.3 Indication of any immediate	me	dical attention and special treatment needed		
Treatment	:	For specialist advice physicians should contact the Poisons Information Service.		
SECTION 5: Firefighting measures				
5.1 Extinguishing media				
Suitable extinguishing media	:	Dry powder Alcohol-resistant foam Carbon dioxide (CO2)		





	No Chang sion Date: 3.2024	ge Service! Date of last issue: 06.09.2022
Unsuitable extinguis media	shing :	Do NOT use water jet.
5.2 Special hazards ari	sing from the	e substance or mixture
Specific hazards du fighting	uring fire- :	Cool closed containers exposed to fire with water spray.
Hazardous combus ucts	tion prod- :	No hazardous combustion products are known
5.3 Advice for firefighte	ers	
Special protective e for firefighters	quipment :	In the event of fire, wear self-contained breathing apparatus.
SECTION 6: Acciden	tal release i	measures
6.1 Personal precautio	ns, protectiv	e equipment and emergency procedures
Personal precautior	าร :	Ensure adequate ventilation. Remove all sources of ignition.
6.2 Environmental pred	cautions	
Environmental prec	autions :	Avoid subsoil penetration.
6.3 Methods and mater	rial for contai	inment and cleaning up
Methods for cleanin	ig up :	Wipe up with absorbent material (e.g. cloth, fleece). Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
6.4 Reference to other see Section 8 + 13	sections	
SECTION 7: Handling	g and stora	ge
7.1 Propositions for sof	io hondling	
7.1 Precautions for saf Advice on safe hand	-	Provide sufficient air exchange and/or exhaust in work rooms.
Advice on protection fire and explosion	n against :	Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. The hot product gives off combustible vapours.
Hygiene measures	:	Keep away from food and drink.
	storage, inc	luding any incompatibilities
Requirements for si areas and containe	-	Store at room temperature in the original container. Do not store at temperatures above 30°C.
Further information age conditions	on stor- :	Keep container tightly closed. Keep away from direct sunlight. Recommended storage temperature: 15 - 25°C
Z11091_18 ZSDB_P_GI	B EN	Page 4/17



by UK REACH Regulations SI 2019/758



terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

Advice on common storage : Do not store together with oxidising agents.

7.3 Specific end use(s)

Specific use(s)

: none

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
propan-1-ol	71-23-8	STEL	250 ppm 625 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The assigned sub- stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA	200 ppm 500 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The assigned sub- stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	GB EH40	

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
Ethanol	Workers	Inhalation	Acute effects, Local effects	1900 mg/m3
	Workers	Skin contact	Chronic effects	343 mg/kg
	Workers	Inhalation	Chronic effects	950 mg/m3
Propan-1-ol	Workers	Skin contact	Long-term systemic effects	136 mg/kg
	Workers	Inhalation	Long-term systemic effects	268 mg/m3
	Workers	Inhalation	Short-term exposure, Systemic effects	1723 mg/m3
propan-1-ol	Workers	Skin contact	Long-term systemic effects	136 mg/kg
	Workers	Inhalation	Long-term systemic effects	268 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	1723 mg/m3
ethanol	Workers	Inhalation	Acute local effects	1900 mg/m3
	Workers	Skin contact	Long-term systemic effects	343 mg/kg
	Workers	Inhalation	Long-term systemic effects	950 mg/m3

Predicted No Effect Concentration (PNEC):



terralin® liquid No Change Service!

Version 06.07 Revision Date: 07.08.2024

Date of last issue: 06.09.2022

schülke ->

Substance name	Environmental Compartment	Value
propan-1-ol	Fresh water	6.83 mg/l
	Soil	1.49 mg/kg
	Marine sediment	2.75 mg/kg
	Fresh water sediment	27.5 mg/kg
	Marine water	0.983 mg/l
ethanol	Fresh water	0.96 mg/l
	Marine water	0.79 mg/l
	Fresh water sediment	3.6 mg/kg
	Soil	0.63 mg/kg
	Marine sediment	2.9 mg/kg
	Sewage treatment plant	580 mg/l


8.2 Exposure controls

Personal protective equipment				
Eye/face protection : Hand protection	Safety glasses with side-shields conforming to EN166			
Directive :	The selected protective gloves have to satisfy the specifica- tions of Regulation (EU) 2016/425 and the standard EN 374 derived from it.			
	Splash protection: disposable nitrile rubber gloves e.g. Dermatril (layer thickness: 0.11 mm) made by KCL or gloves from other manufacturers offering the same protection. Pro- longed contact: Nitrile rubber gloves e.g. Camatril (>120 Min., layer thickness: 0.40 mm) or butyl rubber gloves e.g. Butoject (>480 Min., layer thickness: 0.70 mm) made by KCL or gloves from other manufacturers offering the same protec- tion. Work uniform or laboratory coat. No personal respiratory protective equipment normally re-			
Protective measures :	quired. If the occupational exposure limits cannot be met, in excep- tional cases suitable respiratory equipment should be worn only for a short period of time. Recommended Filter type: A-P2 or ABEK-P2 Respiratory protection complying with EN 141. Avoid contact with skin and eyes.			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

:	liquid colourless alcohol-like not determined
:	Not applicable
:	< -5 °C
	: :



terralin® liquid No Change Service! Version **Revision Date:** Date of last issue: 06.09.2022 06.07 07.08.2024 Decomposition temperature No data available Boiling point/boiling range : ca. 80 °C Flash point 27 °C Method: DIN 51755 Part 1 Evaporation rate No data available Upper explosion limit / Upper : 17.5 %(V) flammability limit Raw material Lower explosion limit / Lower : 2.1 %(V) flammability limit Raw material Vapour pressure ca. 50 hPa (20 °C) : Relative vapour density No data available 2 Density ca. 0.89 g/cm3 (20 °C) Solubility(ies) Water solubility completely soluble (20 °C) 2 Partition coefficient: n-Not applicable 1 octanol/water 425 °C Auto-ignition temperature 2 Raw material Viscositv : not determined Viscosity, kinematic ÷ < 15 s at 20 °C Flow time Method: DIN 53211 Explosive properties No data available : Oxidizing properties The substance or mixture is not classified as oxidizing. • 9.2 Other information Flammability (liquids) Flammable liquid and vapour. 2 Metal corrosion rate None reasonably foreseeable. 5 Self-ignition No data available 1

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



terralin® liquid	No Change Service!
------------------	--------------------

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

	Conditions to avoid	: Heat, flames and sparks.
--	---------------------	----------------------------

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

propan-1-ol:	
--------------	--

propan i on		
Acute oral toxicity	:	LD50 (Rat): ca. 8,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 33.8 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rabbit): 4,032 mg/kg Method: literature value
ethanol:		
Acute oral toxicity	:	LD50 (Rat): 10,470 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat, male and female): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

Components:

propan-1-ol:

Species	:	Rabbit
Result	:	No skin irritation

ethanol:

Species Method Result	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Method	: Expert judgement
Result	: irritating
Remarks	: The toxicological data has been taken from products of similar
	composition.

Components:

propan-1-ol:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

ethanol:

Method	:	OECD Test Guideline 405
Method Result	:	Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

propan-1-ol:

Test Type :	Maximisation Test
Species :	Guinea pig
Method :	OECD Test Guideline 406
Test Type : Species : Method : Result :	Does not cause skin sensitisation.

ethanol:

Test Type Species Method Result	: Maximisation Test : Guinea pig
Method	: OECD Test Guideline 406
Result	: Did not cause sensitisation on laboratory animals.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



6.07	Revision Date: 07.08.2024		Date of last issue: 06.09.2022
	I mutagenicity fied based on availa	able	information.
Compone	ents:		
propan-1	-ol:		
	mutagenicity- As-	:	Not mutagenic in Ames Test
ethanol:			
Genotoxic	sity in vitro	:	Test Type: Microbial mutagenesis assay (Ames test) Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: Not mutagenic in Ames Test
Genotoxia	city in vivo	:	Result: Non mutagenic
Germ cell sessment	mutagenicity- As-	:	Tests on bacterial or mammalian cell cultures did not sho mutagenic effects.
Not classi Compone	fied based on availa ents:	able	information.
propan-1	-ol:		
Carcinoge ment	enicity - Assess-	:	Animal testing did not show any carcinogenic effects.
ethanol:			
Carcinoge ment	enicity - Assess-	:	Did not show carcinogenic effects in animal experiments.
-	ctive toxicity		
	fied based on availa	able	information.
Compone	ents:		
propan-1	n foetal develop-	:	Species: Rat
			Application Route: inhalation (vapour) General Toxicity Maternal: NOAEL: 8.6 mg/l
Effects or ment	tive toxicity - As-	:	
Effects or ment Reproduc	•	:	General Toxicity Maternal: NOAEL: 8.6 mg/l
Effects or ment Reproduc sessment ethanol:	•	:	General Toxicity Maternal: NOAEL: 8.6 mg/l



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

ersion F	No Chang Revision Date: 07.08.2024	Date of last issue: 06.09.2022
sessment		fects.
STOT - single May cause drov	exposure wsiness or dizzine	ess.
Components:		
propan-1-ol:		
Assessment	:	May cause drowsiness or dizziness.
ethanol:		
Remarks	:	No data available
STOT - repeate Not classified b Components:	ed exposure ased on available	information.
propan-1-ol:		
Assessment	:	The substance or mixture is not classified as specific targe organ toxicant, repeated exposure.
ethanol: Remarks	:	No data available
Repeated dos	e toxicity	
Components:		
ethanol:		
Species	:	Rat
NOAEL LOAEL	:	1,730 mg/kg 3,160 mg/kg
Application Rou	ite ·	Oral
Exposure time	:	90 d
Aspiration tox	icity	
Not classified b	ased on available	information.
Further inform	ation	
Product:		
Remarks	:	Inhalation of high vapour concentrations may cause symp- toms like headache, dizziness, tiredness, nausea and vom ing.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to microorganisms	:	EC50 : 68,750 mg/l Method: OECD 209
Components:		
propan-1-ol:		
Toxicity to fish	:	LC50 (Fish): 3,200 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3,642 mg/l Exposure time: 48 h Method: DIN 38412
Toxicity to algae/aquatic plants	:	NOEC (Chlorella pyrenoidosa (algae)): 1,150 mg/l Exposure time: 48 h
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 68.3 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Remarks: Based on data from similar materials
ethanol:		
Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 8,140 mg/l Exposure time: 48 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 5,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
12.2 Persistence and degradabili	ity	

Product:

Biodegradability	:	Result: Readily biodegradable. Method: OECD 301D / EEC 84/449 C6
Components:		

propan-1-ol:		
Biodegradability	:	Test Type: aerobic Result: Readily biodegradable. Biodegradation: 75 % Exposure time: 20 d

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

ethanol:

Biodegradability	:	Test Type: aerobic Result: Readily biodegradable. Biodegradation: > 70 % Exposure time: 5 d Method: OECD 301D / EEC 84/449 C6

12.3 Bioaccumulative potential

Components:

propan-1-ol:		
Bioaccumulation	:	Bioconcentration factor (BCF): 0.88 Remarks: Bioaccumulation is unlikely.
Partition coefficient: n- octanol/water	:	log Pow: 0.2 (25 °C) Method: OECD Test Guideline 117
ethanol:		
Bioaccumulation	:	Remarks: Bioaccumulation is unlikely.
Partition coefficient: n- octanol/water	:	log Pow: -0.14 Method: Calculated value

12.4 Mobility in soil

Components:		
propan-1-ol: Mobility	:	Remarks: Mobile in soils
ethanol: Mobility	:	Remarks: No data available

12.5 Results of PBT and vPvB assessment

Pr	od	uc	t:

Assessment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.Additional ecological infor-: No data is available on the product itself.	tial ered to have endocrine dis REACH Article 57(f) or Co (EU) 2017/2100 or Commi	es not contain components consid- srupting properties according to mmission Delegated regulation ission Regulation (EU) 2018/605 at
--	---	--



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number			
ADR	:	UN 1987	
IMDG	:	UN 1987	
ΙΑΤΑ	:	UN 1987	
14.2 UN proper shipping name			
ADR	:	ALCOHOLS, N.O.S. (propan-1-ol, ethanol)	
IMDG	:	ALCOHOLS, N.O.S. (propan-1-ol, ethanol)	
ΙΑΤΑ	:	Alcohols, n.o.s. (propan-1-ol, ethanol)	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III F1 30 3 (D/E)	
IMDG Packing group Labels EmS Code	::	III 3 F-E, S-D	
IATA (Cargo) Packing instruction (cargo	:	366	



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022	
06.07	07.08.2024		

aircraft) Packing instruction (LQ) Packing group Labels	:	Y344 III Flammable liquid
IATA (Passenger) Packing instruction (passen-		355
ger aircraft)	•	555
Packing instruction (LQ)	:	Y344
Packing group	:	
Labels	:	Flammable liquid

14.5 Environmental hazards

ADR Environmentally hazardous	:	no
IMDG Marine pollutant	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Brit- ain)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable
emissions (integrated p	f 24 November 2010 on industrial pollution prevention and control) unds (VOC) content: 58.27 %
according to Detergents : Other constituents: Per Regulation EC 648/2004	fumes
Other regulations:	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	All components are listed on the inventory, regulatory obliga- tions/restrictions apply
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
ISHL	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	Not in compliance with the inventory
TECI	:	Not in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements				
H225	:	Highly flammable liquid and vapour.		
H318	:	Causes serious eye damage.		
H319	:	Causes serious eye irritation.		
H336	:	May cause drowsiness or dizziness.		
Full text of other abbreviations				
Eye Dam.	:	Serious eye damage		
Eye Irrit.	:	Eye irritation		
Flam. Liq.	:	Flammable liquids		
STOT SE	:	Specific target organ toxicity - single exposure		
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits		
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)		
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)		

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



terralin® liquid No Change Service!

Version	Revision Date:	Date of last issue: 06.09.2022
06.07	07.08.2024	

Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the	e mixture:	Classification procedure:	
Flam. Liq. 3	H226	Based on product data or assessment	
Eye Irrit. 2	H319	Based on product data or assessment	
STOT SE 3	H336	Calculation method	

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.